



**Manufacturing Company**

4540 W. Thomas Street • Chicago, IL 60651-3318

Telephone: 773-227-3700

Wats: 800-252-5796

Fax: 773-227-3705

E-mail: info@blackswanmfg.com

Web Site: www.blackswanmfg.com

February 1, 2011

# NEW PRODUCTS Wholesale Price Sheet

**CATEGORY**

**2**

## Pipe Joint Compounds & PTFE Tape/Packing

<b>Product</b>	Stock No.	Size	Packing	Wt. Per Case-Lbs.	List Price Each	Wholesale Price Each
<b>BIG WHITE</b> - A soft set, non-hardening, smooth, grit-free, homogenized PTFE pipe joint compound. For use on metal and plastic threaded connections. Formulated to be used on all types of systems carrying most any gas or liquid except oxygen, fluorine and liquid sodium. Will not transfer any taste or odor to the system being sealed. Excellent for food and water systems. Temperature range for gasses and liquids: -50°F(-45° C) to +400° F (+204° C). Pressure range for gasses up to 3,000 PSI, liquids up to 10,000 PSI. Brushable to: -50° F (-45° C). Contains no lead or silicone.	02082	5 gal.	1	75	517.53	233.12
<b>PTFE TAPE - YELLOW - GAS LINE</b> A heavy duty, high density PTFE tape especially recommended for gas lines. Can be used on lines carrying natural gas, propane, water, oil, etc. Thickness is .0035 ± .0005, pressure rating of 10,000 PSI and withstands temperature from -450° F to 500° F. Can be used on oxygen systems. Meets Federal Specification MIL-T-27730A. UL listed.	02142	3/4" x 520"	12	1	6.04	2.72
<b>PTFE TAPE - PINK - WATER LINE</b> A high density PTFE tape, 0.7 density and thickness of .0035 ±.0005. Meets Federal Specification MIL-T-27730A. Temperature range from -450° F to 500° F.	0 2146 0 2148	1/2" X 520" 3/4" X520"	12 12	1 1	3.93 4.97	1.77 2.24
<b>PTFE TAPE - GRAY - STAINLESS STEEL</b> A high density PTFE tape, 0.7 density and thickness of .0035 ±.0005. Meets Federal Specification MIL-T-27730A. Temperature range from -450° F to 500° F.	02152 02154	1/2" X 520" 3/4" X520"	12 12	1 1	3.93 4.97	1.77 2.24
<b>PTFE TAPE - GREEN - OXYGEN LINE</b> A high density PTFE tape, 0.7 density and thickness of .0035 ±.0005. Meets Federal Specification MIL-T-27730A. Temperature range from -450° F to 500° F.	02162 02164	1/2" X 520" 3/4" X520"	12 12	1 1	3.93 4.97	1.77 2.24
<b>PTFE TAPE - LOW DENSITY - U.S.A.</b> A high density PTFE tape, 3.7 density and thickness of .0035 ±.0005. Meets Federal Specification MIL-T-27730A. Temperature range from -450° F to 500° F.	02220 02225 02230 02235	1/2" X 260" 1/2" X 520" 3/4" X520" 1" X 520"	24 24 24 24	1 1 1 2	1.89 2.42 3.73 4.46	0.85 1.09 1.68 2.01

EXISTING PRODUCT  
NEW  
STOCK NUMBERS

**CATEGORY**

**4**

## Wax Gaskets, Cold Solders & Lubricants

<b>Product</b>	Stock No.	Size	Packing	Wt. Per Case-Lbs.	List Price Each	Wholesale Price Each
<b>SILICONE GREASE</b> A 90% pure silicone product that contains no petroleum additives and offers heat resistance up to 450° F. Non-staining. Apply to rubber and synthetic o-rings.	04130	5 gal.	1	45	2,142.30	965.00

**GATEGORY**

**9**

**Drain & Waste System Cleaners**

**Product**

	Stock No.	Size	Packing	Wt. Per Case-Lbs.	List Price Each	Wholesale Price Each
<b>HEAVY DUTY LIQUID BUILD-UP REMOVER</b> Five times faster and stronger than regular Liquid Build-Up Remover. Contains 50 billion active enzyme producing units per quart. One of the strongest biological products on the market today.	09046	1/2 gal.	6	42	17.76	8.00
	09047	gal.	4	56	33.30	15.00
	09048	5 gal.	1	70	129.78	58.46
<b>POWER CRYSTALS</b> Drain pipe opener in crystal form. For use on clogged drains, grease traps and septic systems.	09175	1 lb.	12	13	8.33	3.75
	09177	2 lb.	12	26	16.10	7.25
	09179	6 lb.	4	25	45.51	20.50
	09181	25 lb.	1	26	143.82	64.78
	09183	50 lb.	1	52	266.40	120.00

EXISTING PRODUCT  
NEW STOCK NUMBERS

**GATEGORY**

**10**

**Cloth & Accessory Items**

**Product**

	Stock No.	Size	Packing	Wt. Per Case-Lbs.	List Price Each	Wholesale Price Each
<b>DUCT TAPE - BLACK</b> A polyethylene coated cloth backed tape. Has excellent adhesion and tack. High tensile strength and conforms well to irregular surfaces. Ideal for sealing duct work, general purpose packaging and masking PVC pipe. Thickness is 8.5 mil.	10056	2" x 60 yds.	24	39	12.48	5.62
<b>ALL PURPOSE SHOP TOWELS</b> Paper towels. Cloth like, soft on hands and face. Ideal for all medium to heavy-duty general purpose wiping applications and are perfect for jobs that require larger towels. The dispenser box can dispense from either the top or bottom. The dispenser box is portable, protects towels and allows for single sheet dispensing.	10090	9-1/2" x 16-1/8"	100	3	.16	.07

**GATEGORY**

**13**

**Toilet Bowl Accessories**

**Product**

	Stock No.	Size	Packing	Wt. Per Case-Lbs.	List Price Each	Wholesale Price Each
<b>BOWL TO WALL GASKET KIT - WALL HUNG CLOSET</b> An expanded closed cell chemical resistant foam gasket with guide ring and special adhesive tape, especially designed to eliminate the leakage often encountered with inferior foam rubber gaskets. It is resistant to water, petroleum products, chemicals and similar substances. Will not rot.	13180	_____	6	1	26.64	12.00

**GATEGORY**

**17**

**Plumbing Construction Materials**

**Product**

	Stock No.	Size	Packing	Wt. Per Case-Lbs.	List Price Each	Wholesale Price Each
<b>ECONOMY TEST PLUGS</b> Inexpensive test plugs for low-pressure testing. The bottom and top are stamped steel plates and there is a rubber gasket in-between, which will expand to seal the pipe when the wing nut is tightened.	17160	1-1/2"	12	3	2.82	1.27
	17165	2"	12	3	3.17	1.43
	17170	3"	12	6	4.68	2.11
	17175	3-1/2"	12	6	6.84	3.08
	17180	4"	12	9	5.77	2.60
	17185	5"	12	13	12.92	5.82
	17190	6"	12	21	13.32	6.00