



GEORG FISCHER
PIPING SYSTEMS



Georg Fischer Harvel LLC
300 Kuebler Road
Easton, PA 18040
USA
Phone: (610) 252-7355
Fax: (610) 253-4436
harvel.gfh.ps@georgfischer.com
www.harvel.com

PRICES SUBJECT TO CHANGE WITHOUT NOTICE
PRICE SHEET EFFECTIVE 09/27/10
REVISED 03/19/12

Price List

PVC SCHEDULE 40 CLEAR PIPE

NOMINAL PIPE SIZE	AVG. O.D.	AVG. I.D.	MIN. WALL	MAX. W.P. P.S.I.*	LBS/FT	LGTHS/ CARTON	LIST PRICE PER FT
1/4"	.540	.354	.088	390	.081	10	.97
3/8"	.675	.483	.091	310	.109	10	1.31
1/2"	.840	.608	.109	300	.161	35	1.96
3/4"	1.050	.810	.113	240	.214	25	2.63
1"	1.315	1.033	.133	220	.315	25	3.89
1-1/4"	1.660	1.364	.140	180	.426	20	5.27
1-1/2"	1.900	1.592	.145	170	.509	16	6.31
2"	2.375	2.049	.154	140	.682	12	8.50
2-1/2"	2.875	2.445	.203	150	1.076	8	13.43
3"	3.500	3.042	.216	130	1.409	6	17.54
3-1/2"	4.000	3.520	.226	120	1.697	4	22.28
4"	4.500	3.998	.237	110	2.006	4	26.41
5"	5.563	5.017	.258	95	2.726	1	36.89
** 6" x 1/8"	6.625	6.355	.110	45	1.647	1	30.62
6"	6.625	6.031	.280	90	3.535	1	48.28
8"	8.625	7.943	.322	80	5.305	1	72.40
10"	10.750	9.976	.365	70	7.532	1	116.55
12"	12.750	11.890	.406	70	9.949	1	153.95

CLEAR CEMENT & PRIMER

#705 CLEAR CEMENT	P-70 CLEAR PRIMER
17.14 Pint	14.75 Pint
29.29 Quart	23.84 Quart

Standard Length – 10 Feet. Custom lengths and sizes are available. Contact factory for information.

All pipe is packed in polybags and boxed – sold in carton quantities only.

This material complies with the provisions of Title 21 of the United States FDA Code of Federal Regulations, and is safe for use in food contact applications.

Pipe has a UL 94 V-O rating.

* For water at 73.4 F. with solvent welded joints.

** This size does not meet schedule 40 criteria.

Sales policy: See sheet "Terms of Sale."

Standard threading or grooving of Harvel® Schedule 40 Clear pipe is not recommended due to insufficient wall thickness. Use specialty clear transition fittings for threaded assemblies or standard PVC transition fittings where applicable.



Georg Fischer Harvel LLC
300 Kuebler Road
Easton, PA 18040
USA
Phone: (610) 252-7355
Fax: (610) 253-4436
harvel.gfh.ps@georgfischer.com
www.harvel.com

PRICES SUBJECT TO CHANGE WITHOUT NOTICE
PRICE SHEET EFFECTIVE 09/27/10
REVISED 03/19/12

PRICE LIST

PVC SCHEDULE 80 CLEAR PIPE

NOMINAL PIPE SIZE	AVG. O.D.	AVG. I.D.	MIN. WALL	MAX. W.P. P.S.I.*	LBS/FT	LGTHS/ CARTON	LIST PRICE PER FT
1/4"	.540	.288	.119	570	.100	10	1.23
3/8"	.675	.407	.126	460	.138	10	1.70
1/2"	.840	.528	.147	420	.202	35	2.49
3/4"	1.050	.724	.154	340	.273	25	3.36
1"	1.315	.935	.179	320	.402	20	4.95
1-1/4"	1.660	1.256	.191	260	.554	12	6.82
1-1/2"	1.900	1.476	.200	240	.673	10	8.29
2"	2.375	1.913	.218	200	.932	6	11.47
2-1/2"	2.875	2.289	.276	210	1.419	5	17.48
3"	3.500	2.864	.300	190	1.903	4	23.44
4"	4.500	3.786	.337	160	2.782	3	34.26
6"	6.625	5.709	.432	140	5.313	1	65.44

*PSI water, non-shock @ 73°F with solvent welded connections.

Standard Length – 10 Feet ±1". Custom lengths, sizes and belled ends are available; contact factory for details. Sold in carton quantities only. All pipe is sleeved in polybags and boxed on-line to avoid scratching and maintain cleanliness.

Harvel expands the quality line of Clear products to include pipe produced to heavy wall Schedule 80 dimensions. This permits the use of Clear products in more demanding applications. Technological advancements have enabled the production of heavier wall products without jeopardizing clarity. This provides pipe with higher pressure bearing capability than schedule 40 Clear, while maintaining optimal clarity.

Harvel Sch 80 Clear pipe is compatible with standard PVC pipe fittings and valves. Pressure ratings shown are dependent on temperature; use standard PVC de-rating factors for use at elevated temperatures.

Maximum temperature use is 140°F. Harvel Sch 80 Clear can be threaded using standard threading practices; maximum temperature for threaded systems should not exceed 110°F. Threaded pipe requires a 50% reduction in pressure ratings shown.

Material used in the manufacture of this pipe complies with the provisions of Title 21 of the United States FDA Code of Federal Regulations, and is safe for use in food contact applications.

Refer to publication HPB-107 Clear pipe brochure for additional information pertaining to materials, physical properties, and installation information.

Max. Support Spacing

Size	Temperature (°F)				
	73	80	100	120	140
1/4"	4	4	3-1/2	2-1/2	2
3/8"	4-1/2	4-1/2	4	2-1/2	2-1/2
1/2"	5	4-1/2	4-1/2	3	2-1/2
3/4"	5-1/2	5	4-1/2	3	2-1/2
1"	6	5-1/2	5	3-1/2	3
1-1/4"	6	6	5-1/2	3-1/2	3
1-1/2"	6-1/2	6	5-1/2	3-1/2	3-1/2
2"	7	6-1/2	6	4	3-1/2
2-1/2"	7-1/2	7-1/2	6-1/2	4-1/2	4
3"	8	7-1/2	7	4-1/2	4
4"	9	8-1/2	7-1/2	5	4-1/2
6"	10	9-1/2	9	6	5