

**Mortar Drain**

**U.S. Patent #5,216,767**

**Mortar Drain is a porous filter designed to protect the weep holes located in the clamping ring collar of the floor drain. The filter keeps the weep holes and collar surface clear of mortar. The porosity of the filter keeps the weep holes and collar surface clear of mortar while allowing rapid water flow through.**

Notice: This filter is not a water proof device. In no event should the seller or the manufacturer of this filter be liable for any damages caused by a leaking shower.

**MORTAR DRAIN**



- **Installs over weep holes on shower drain**
- **Porosity promotes flow to weep holes**
- **Protects weep holes from mortar clog**

**Installation Instructions:** Lay the Mortar Drain filter over the "TOP" of the floor drain clamping ring collar. (ON THE TOP OF THE WEEP HOLES). The filter should lay flat over the clamping ring, fitting around any bolt heads that might be located on the top of the collar.


**WARNING:** Do not install filter underneath clamping ring, this will cause the shower to leak.

<u>Part No.</u>	<u>Description</u>	<u>Case Qty.</u>
UNIV-1	Universal Mortar Drain	84
DS62	Mortar Drain for DaL-DraiNs (D2T,DD23T)	84

**MOLD PREVENTATIVE**

Model UNIV 1 (Universal Model) Fits most shower drains

- Bolt hole "A" is used with all drains.
- For drains with 4 bolts, remove A and B holes.
- For drain with 3 bolts remove A and C holes.
- For drains with larger diameter necks, tear out the inner radius (circle).



Follow all recommended procedures for placement of a shower floor mortar bed in the Tile Council of America handbook and Uniform Plumbing Code Standard IS-4. Mortar installer should be experienced in installation of mortar beds, drains, and shower floors. A minimum of one and one-half inches of compacted reinforced mortar should be placed over the Mortar Drain. Failure to follow these procedures could result in an ineffective installation or weak mortar bed. NOTE: Because the installation of the mortar bed and floor is beyond our control, we will not be responsible for results obtained.

The Uniform plumbing Code label UPC is a registered trademark of the International Association of Plumbing and Mechanical Officials, (IAPMO). Mortar Drain has been tested to exceed the IAPMO requirements for "Porous Filter Protection for Sub-Drain weep holes" and is a listed product with IAPMO.

**LIMITED WARRANTY**

Since the installation of this product is beyond the control of the manufacturer and the seller, the liability of the manufacturer and sellers shall be limited to replacement of the product. The manufacturer warrants that the "Mortar Drain" is manufactured free of defects in material and workmanship. DUE TO THE VARYING CONDITIONS UNDER WHICH THIS PRODUCT IS USED OR INSTALLED, THE MANUFACTURER OFFERS NO WARRANTY AS TO THE LENGTH OF SERVICE OR SUITABILITY FOR ANY PARTICULAR PURPOSE, OF MERCHANTABILITY OR ANY OTHER WARRANTY, WHETHER EXPRESSED OR IMPLIED, ORAL OR WRITTEN, IN NO EVENT SHALL DALLAS SPECIALITY BE LIABLE FOR INCIDENTAL, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES. WHETHER DUE TO BREACH OF WARRANTY, CONTRACT OR NEGLIGENCE. Any action for breach must be brought within 30 days of delivery. The manufacturer retains the right to make changes or improvements to the product from time to time.